

FLORSTRIP A

**LOW FOAM FLOORSTRIPPER AS WELL AS
A HEAVY DUTY DEGREASER IN THE FOOD INDUSTRY**

PRODUCT USE:

FLORSTRIP A is a wax and polymer stripper for floors as well as an excellent degreaser for cleaning food service equipment, exhaust hoods and other surfaces subjected to heavy grease build-up.

ADVANTAGES:

- **FLORSTRIP A** dissolves the toughest types of soil, even those not soluble in water.
- **FLORSTRIP A** emulsifies the soil so that it can be removed by rinsing.
- Can be used on glass, aluminium, concrete, quarry tiles, metal ducts, grills and machinery.
- Can be used with hot, cold, hard and soft water.
- It is sprayable.
- It is non-flammable.
- **FLORSTRIP A** is rust inhibited and is non-irritating to normal skin.
- **FLORSTRIP A** is specially designed for self propelled auto scrubbers and single-disc scrubbing machines.
- It is concentrated and economical.

PRODUCT DESCRIPTION:

Form:	Liquid	Biodegradable:	Yes
Colour:	Green	Foam:	Low
Odour:	Slight Ammonia	pH:	Alkaline

DIRECTIONS FOR USE:

Floor stripping - Single disc scrubbing machine:

For removing wax or synthetic finishes:

Dilute 1 litre of **FLORSTRIP A** in 5 litres of water. Apply the solution to the floor and let soak for approximately 5 minutes until the wax starts to whiten and emulsify. Scrub thoroughly with a nylon scrubbing pad or steel wool. As soon as the wax or the synthetic finish has been loosened, pick up with a vacuum or mop. RINSE thoroughly, improper rinsing is useless. Any residue of the stripper will cause a poor bond of the new floor polish to the surface and in addition can react with the polish. Add 250 ml of vinegar to 10 litres of water and apply to the just stripped floor to neutralise any residual alkalinity left from the stripping operation. Pick up with a wet vacuum or dry up the floor using a wring-out mop. Rinse with clean warm water. Let the floor dry thoroughly before applying

FLORSHINE.

AUTO SCRUBBING MACHINES:

Stripping with an auto-scrubber is a two pass operation. The stripping solution must be left on the floor for 5 minutes to chemically soften the old hard wax or synthetic finish.

Step 1: Mix 2 litres of **FLORSTRIP A** to each 10 litres of water. Start brushes revolving. Open stripper solution lever. Throw in clutch for forward movement. Wet and scrub down 45 sqm metres of floor area.

Step 2: Return to the starting position. Close the stripper solution lever. Lower the stripping brushes and the vacuum pick up. Throw in the clutch for forward movement. Strip the entire area that was covered in Step 1. Apply sufficient rinse water, to rinse properly. With lowered brushes, solution feed shut-off, vacuum off all the rinse water. Once all the stripper has been thoroughly rinsed off allow the floor to dry well.

NOTE: Not to be used as a daily cleaner on any floor coverings with synthetic or carnuba waxes.

AUTOMATED SPRAY DEGREASING:

1. Mix 2 parts **FLORSTRIP A** to 1 part warm.
2. Fill a pressure can with the solution.
3. Spray on the heavily soiled areas or where grease has been baked on. Leave to penetrate for a few minutes. Agitate soiled area with a stiff brush.
4. Rinse off well with clear water.
5. Allow to air dry.

Ref. No. 11/17

PRECAUTIONS:

Keep out of reach of children. Do not swallow. Avoid contact with eyes. Contains Ammonia.

FIRST AID:

External: Immediately flush skin with plenty of water.
Eyes: Immediately flush eyes with plenty of water for at least 15 minutes.
Internal: If swallowed, immediately drink a large quantity of water.
GET MEDICAL ATTENTION IMMEDIATELY!

Every endeavour has been made to ensure that the information in this data Sheet is reliable, but we do not accept any liability for any loss, injury or damage which may result from its use