

# HEAVY FUEL ADDITIVE

## SOOT AND SLUDGE PREVENTION WHEN BURNING HEAVY FUEL OIL

### PRODUCT USE:

- Prevents sludge in the fuel oil tanks and lines by emulsifying the sludge and burning it off.
- Minimizes line deposit as it lowers viscosity of fuel oil and allows easier flow – particular in winter.
- Improves combustion of fuel oil by better atomization of the nozzle.
- Minimized fireside deposits.
- Contains catalysts which lower the irrigation points of sulphur and vanadium contaminates so that they burn off.

### DIRECTIONS FOR USE:

- 1: 2000 for the first month
- 1: 4000 for the second month – and thereafter

Where a very badly sludged system is encountered 1 part of HFA to 100 part fuel oil can be used. Premix 1 part of HFA to 20 parts of fuel oil. Add to the fuel tank before refilling.

### PRODUCT DESCRIPTION:

Appearance: Clear, dark, thin liquid.  
S.G.: 1,04 ± 0,01

*Ref. No. 11/17*

### PRECAUTIONS:

Keep out of reach of children.

### FIRST AID:

- Inhalation: Move to warm area and administer oxygen
- Eye contact: Flush eyes immediately with cool running water for at least 15 minutes. Obtain medical attention.
- Ingestion: Drink plenty of milk or water. GET MEDICAL ATTENTION!

Every endeavour has been made to ensure that the information in this Data Sheet is reliable, but we do not accept any liability for any loss, injury or damage which may result from its use.