

Woodoc 2000 Specification Sheet



Typical Application:

Woodoc 2000 is recommended for indoor finishes only, and is suitable for all furniture applications. **Not suitable for use on floors.**

Product Features:

Woodoc 2000 is a quick drying, economical and tough single coat sealer. Woodoc 2000 may be applied by spray gun or by brush. Apply one liberal spray coat, ensuring that the surface of the timber is evenly wet all over, and remains evenly wet all over for 10 minutes after coating. Re-wet any dull spots. The same application method may be followed for brush coating, but be careful of brush marks due to the quick drying nature of Woodoc 2000. Woodoc 2000 yields a very hard, scratch-resistant finish. Woodoc 2000 is also compatible with all Woodoc Colours and Stain Concentrate additives. **Note: The adding of Woodoc Colours or Woodoc Stain Concentrates may retard the drying process however.**

- Quick drying: 30 minutes – 1 hour – depending on atmospheric conditions.
- Allow 18 – 24 hours until hard dry.
- Dilute only with 10% mineral turpentine.
- One coat spray or brush-on application.
- Fills the wood grain.
- Available in gloss or low gloss finish.
- Water-, heat-, stain and alcohol-resistant.
- Non-toxic when dry.
- Does not affect glue.
- Complete how-to-use instructions on label.

No: WD2000/003

Dated: 07/10/11

Name:

Woodoc 2000 - Professional Wood Finishing Sealer

Description:

Clear; Fast Drying; One-Coat; Spray or brush application; Gloss or low gloss finish.

Coverage:

± 8 m² per litre, depending on wood porosity and coat thickness.

Application:

Spraying recommended. Brush can also be used. Clean brush and spray equipment with mineral turpentine.

Dilution:

Dilute the product with mineral turpentine only, to a maximum of 10%.

Drying Time:

Handling: 30 minutes to one hour.

Hard: Allow 18 – 24 hours until hard dry.

Drying will vary, depending on moisture and atmospheric conditions.

Product Properties:

Clear, lead-free indoor wood sealer.

Wax Content:

None

Compatibility:

Mineral Turpentine.

Non-Compatibility:

Acetone, Lacquer Thinners, Benzene and other solvents.

Packaging:

1 litre, 5 litres. (20 or 200 litres available on request from dealer)

ALWAYS READ THE DIRECTIONS ON THE TIN BEFORE APPLICATION.

FLAMMABLE. Keep out of reach of children. Harmful when consumed. Ingestion may cause chemical pneumonitis. IMPORTANT: This product hardens through contact with air (oxygen). Replace lid firmly after use to prolong pot life.



Manufactured and marketed by:

Rekara Mills (Pty) Ltd

PO Box 16, Fort Beaufort 5720, South Africa

Tel +2746 645 1109 Fax +2746 645 1538

Customer Service:

Toll-Free during office hours 0800 411 200 (South Africa only)

E-mail: information@woodoc.com or visit www.woodoc.com