

# Woodoc 55 Specification Sheet



## Typical Application:

For exterior use where a tinted, gloss sealer is required. Provides UV-protection and is water repellent. It is used extensively on yachts, boats and all exterior woodwork on buildings exposed to conditions of harsh weathering.

**Not suitable for use on hard, dense wooden decks.**

## Product Features:

Woodoc 55 is a tinted, exterior gloss sealer with UV-absorbers and added transparent iron oxides to protect wood against harsh sunlight.

- Excellent protection against wind, water, pollution and salt spray.
- Contains a special alkyd base that remains flexible, preventing surface cracking associated with temperature variation.
- Superior Ultra-violet radiation protection in extreme conditions.
- High-build characteristic for a smooth gloss surface.
- Available in three tints: Meranti, Russet and Deep Brown.
- Suitable for all wood types.
- Non-toxic when dry.
- Does not affect glue.
- Deep penetrates to nourish wood.
- Biodegrades at the end of its life cycle.
- Complete how-to-use instructions on label.

**No:** WD55/002

**Dated:** 01/12/11

## Name:

Woodoc 55 - Exterior Gloss Sealer (Meranti / Dark Brown / Russet)

## Description:

Deep penetrating, tinted, gloss finish with UV protection and water repellence, for outdoor use.

## Coverage:

First coat 10-12 m<sup>2</sup>/litre. Subsequent coats 12-14 m<sup>2</sup>/litre. 3 coats (average) 3,3 m<sup>2</sup>/litre.

## Application:

By brush. Clean brush with mineral turpentine.

## Dilution:

Dilution is not recommended, but should dilution be necessary, use only mineral turpentine.

Drying will vary, depending on moisture and atmospheric conditions.

## Product Properties:

Tinted, gloss, high-build, exterior wood sealer. Formaldehyde-Free

## Wax Content:

None.

## Compatibility:

Mineral Turpentine.

## Non-Compatibility:

Acetone, Lacquer Thinners, Benzene, and other solvents.

## Packaging:

500 ml, 1 litre and 5 litres. (20 or 200 litres available on request from dealer)

**ALWAYS READ THE DIRECTIONS ON THE TIN BEFORE STARTING WORK.**

**FLAMMABLE. Keep out of reach of children. Harmful when consumed. Ingestion may cause chemical pneumonitis.**

**IMPORTANT: This product hardens through contact with air (oxygen). Replace lid firmly after use to prolong pot life.**



Manufactured and marketed by:

Rekara Mills (Pty) Ltd

PO Box 16, Fort Beaufort 5720, South Africa

Tel +2746 645 1109 Fax +2746 645 1538

Customer Service:

Toll-Free during office hours 0800 411 200 (South Africa only)

Email: [information@woodoc.com](mailto:information@woodoc.com) or visit [www.woodoc.com](http://www.woodoc.com)