

Woodoc Deck Dressing Specification Sheet



Typical Application:

A tinted, matt oil finish for exterior application to hard, dense timber decking like Balau, Rhodesian Teak, Garapa or Iroko. Also suitable for roughly-sawn wood, e.g. wendy houses and fences. Recommended re-application: every 6 months or when wood looks dry.

Product Features:

Woodoc Deck Dressing is oil-based with added transparent iron oxides to protect wood against harsh sunlight.

- Excellent wind, water, pollution and salt spray protection.
- Incorporates a special drying oil that remains flexible.
- Superior ultra-violet radiation protection in extreme conditions and is water-repellent.
- Low build characteristic for a smooth and attractive matt surface.
- Available in Golden Brown, Rich Meranti and Deep Brown.
- Penetrates deeply to nourish wood.
- Non-toxic when dry.
- Does not affect glue.
- Bio-degrades at the end of its life cycle.
- Complete how-to-use instructions on label.

No: WDD/004

Dated: 15/09/16

Name: Woodoc Deck Dressing – Exterior Matt Oil Finish (Rich Meranti / Deep Brown / Golden Brown)

Description:

Tinted, matt finish with UV-protection and water repellence, for outdoor use.

Coverage:

First coat 10-12 m²/litre. Subsequent coats 12-14 m²/litre. 3 coats (average) 3,3 m²/litre.

Application:

By brush. Clean brush with mineral turpentine.

Dilution:

Dilution is not recommended, but should dilution be necessary, use only mineral turpentine.

Drying Time:

The different coats may take up to 48 hours to dry, depending on the weather. **Caution:** As the product does not form a hard film on the surface, shoes and furniture cushions could be affected for at least 48 hours after application.

Product Properties:

Tinted, matt, exterior oil finish.

Wax Content:

Medium.

Compatibility:

Mineral Turpentine. **Non-Compatibility:** Acetone, Lacquer Thinners, Benzene, and other solvents.

Packaging:

1 litre, 2,5 litres and 5 litres. (20 or 200 litres available on request from dealer)

ALWAYS READ THE DIRECTIONS ON THE TIN BEFORE STARTING WORK.

FLAMMABLE. Keep out of reach of children. Harmful when consumed. Ingestion may cause chemical pneumonitis. **IMPORTANT:** This product hardens through contact with air (oxygen). Replace lid firmly after use to prolong pot life.



Manufactured and marketed by:

Rekara Mills (Pty) Ltd

PO Box 16, Fort Beaufort 5720, South Africa

Tel +2746 645 1109 Fax +2746 645 1538

Customer Service:

Toll-Free during office hours 0800 411 200 (South Africa only)

E-mail: information@woodoc.com or visit www.woodoc.com